

RETAIL PRICE SHEET



April, 2023

WIREWORLD®
CABLE TECHNOLOGY

Engineered
for
Reality™

All prices shown are in Euro.
VAT is included

Because we are continually striving to improve our products, all specifications and prices are subject to change without notice.

TWINAX ETHERNET CABLES		Materials		Cable design	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	10.0m (32.8 ft.)			
Patented noise-isolating design. Longer lengths provide greater improvements.												
CHROMA 8 (CHE)		23 ga. oxygen-free copper COMPOSILEX® 3		Tite-Shield™ patented triple-shielded design	120	150	180	250	390			
COAXIAL DIGITAL AUDIO CABLES (75 ohms, RCA plugs, BNC's optional)		Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)	
CHROMA 8 (CRV)		oxygen-free copper	COMPOSILEX® 3	DNA Helix®	24K gold / OFC	45	50	52	55	63	85	
ULTRAVIOLET 8 (UVV)		silver-plated OFC	COMPOSILEX 3	DNA Helix	24K gold / OFC	79	85	90	100	110	145	
STARLIGHT 8 (STV)		silver-clad OFC	COMPOSILEX 3	DNA Helix	silver-clad OFC	125	150	175	200	245	390	
SILVER STARLIGHT 8 (SSV)		OCC-7N silver-clad copper	COMPOSILEX 3	DNA Helix	silver-clad OFC	300	350	420	480	600	960	
GOLD STARLIGHT® 8 (GSV)		solid silver	COMPOSILEX 3	DNA Helix	silver-clad OFC	510	720	930	1,150	1,550	2,800	
USB AUDIO CABLES (All models exceed official USB specifications) 90-0hm impedance			Conductor material	Insulation material	Cable design	0.3m (1 ft.)	0.6m (2 ft.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)		
2.0	ULTRAVIOLET™ 8 USB 2.0 A to B (U2AB)		silver-plated OFC	COMPOSILEX 3	Uni-Path Isolated power conductor		60		80	90		
3.0	CHROMA 8 USB 3.0 A to B (C3AB)		OFC	COMPOSILEX 3	Uni-Path Isolated power conductor		50	52		66		
3.0	STARLIGHT 8 USB 3.0 A to B (S3AB)		silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor			150				
NOTE: Wireworld Power Cords function as filters, so longer lengths provide greater improvements. We recommend two meters or more for the best performance.												
POWER CONDITIONING CORDS – Ultra-quiet, dynamic and flexible. Standard: US, EU, UK wall plug to IEC C13. VDE certified for safety. C19 or PowerCON custom termination available for upcharge.			Conductor material	Insulation material	Cable design	Plug contact material	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)		
STRATUS™ 7 Power Cord (STP)				oxygen-free copper	COMPOSILEX® 2	Fluxfield™	silver-clad copper alloy	125	155	185	240	
SILVER ELECTRA™ 7 Power Cord (SEP)				OCC-7N silver-clad copper	COMPOSILEX 2	Fluxfield	silver-clad copper alloy			900	1,200	
AUDIO INTERCONNECT PAIRS (2 RCA males to 2 RCA males)		Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m pair (20 in.)	1.0m pair (40 in.)	1.5m pair (5 ft.)	2.0m pair (6.5 ft.)	3.0m pair (10 ft.)	6.0m pair (20 ft.)	
LUNA™ 8 (LUI)			oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	24K gold/OFC	78	85	90	96	110	145
SOLSTICE® 8 (SOI)			silver-plated OFC	COMPOSILEX 3	Tri DNA Helix	24K gold/OFC	100	120	133	150	175	260
OASIS® 8 (OAI)			oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver-clad OFC	155	180	205	230	275	420
EQUINOX® 8 (EQI)			OCC-7N copper	COMPOSILEX 3	Tri DNA Helix	silver-clad OFC	230	300	370	445	590	1,000
ECLIPSE™ 8 (ECI)			OCC-7N copper	COMPOSILEX 3	Quad DNA Helix	silver-clad OFC	480	610	750	900	1,180	2,040
SILVER ECLIPSE™ 8 (SEI)			OCC-7N silver-clad copper	COMPOSILEX 3	Quad DNA Helix	silver-clad OFC	630	920	1,200	1,495	2,070	3,800

BALANCED INTERCONNECT PAIRS (2 XLR females to 2 XLR males)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m pair (20 in.)	1.0m pair (40 in.)	1.5m pair (5 ft.)	2.0m pair (6.5 ft.)	3.0m pair (10 ft.)	6.0m pair (20 ft.)
LUNA 8 (LBI) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	115	120	125	132	145	180
SOLSTICE 8 (BSI) 	silver-plated OFC	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	135	150	163	177	205	295
OASIS 8 (OBI) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	180	205	230	250	300	450
EQUINOX 8 (QBI) 	OCC-7N copper	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	230	300	370	450	580	1,050
ECLIPSE 8 (EBI) 	OCC-7N copper	COMPOSILEX 3	Quad DNA Helix	silver/copper alloy	480	620	780	920	1,230	2,130
SILVER ECLIPSE 8 (SBI) 	OCC-7N silver-clad copper	COMPOSILEX 3	Quad DNA Helix	silver/copper alloy	630	920	1,200	1,495	2,050	3,800

Thank You

We appreciate your business.

